






Learn more about
this product




Your Gateway to Efficient Connectivity

The Q-Cable is a 0.3 m (0.98 ft) long adapter cable for the Kvaser PC1canx 4xHS and Kvaser PC1can 4xHS boards. A DSUB pin connector connects to the PC1can board, whilst four DSUB pin connectors connect to the CANbus.

 **Warranty**
2-Year warranty. See our general conditions and policies for details.

 **Support**
Free support for all products by contacting support@kvaser.com

 **EAN**
73-30130-00199-2

Major Features

- Adapter cable designed for the Kvaser PCICanx 4xHS and the Kvaser PCICan 4xHS boards.
- One molded 25 pin DSUB connector with thumbscrews that connects to the CAN interface board.
- Four molded 9 pin DSUB connectors with thumbscrews for the CAN bus.
- The Q-cable is also available in a 3 meter length low smoke zero halogen version (Item no. 00340-8) to protect people and equipment from toxic and corrosive gases.
- Compatible with J1939, CANopen, NMEA 2000® and DeviceNet. Higher layer protocol translation handled by the user's application. For software support please see our Technical Associates products and our Software Download page (www.kvaser.com).

Support

Documentation, Kvaser CANlib SDK and drivers can be downloaded for free at www.kvaser.com/downloads.

Kvaser CANlib SDK is a free resource that includes everything you need to develop software for the Kvaser CAN interfaces. Includes full documentation and many program samples, written in C, C++, C#, Delphi, Visual Basic, Python and t programming language.

Kvaser CAN hardware is built around the same common software API. Applications developed using one device type will run without modification on other device types.

Technical Data

CAN Channels	4
Certificates	CE, RoHS
Connector	One 25 pin DSUB Four 9 pin DSUB
Length	300 mm
Material	Durable thermoplastic rubber
Operating Temperature Range	-30 to +85 °C
Weight	140 g