











Your Gateway to Efficient Connectivity

The Q-Cable is a 3 m (9.8 ft) long adapter cable for the Kvaser PCIcanx 4xHS and Kvaser PCIcan 4xHS boards. A DSUB pin connector connects to the PCIcan board, whilst four DSUB pin connectors connect to the CANbus. This variant helps to protect people and equipment from toxic and corrosive gasses by emitting limited smoke and no halogen when exposed to high heat sources.

Warranty

2-Year warranty. See our general conditions and policies for details.

Support

Free support for all products by contacting support@kvaser.com

[II] EAN

73-30130-00340-8





Major Features

- Adapter cable designed for the Kvaser PCIcanx 4xHS and the Kvaser PCIcan 4xHS boards.
- One molded 25 pin DSUB connector with thumbscrews that connects to the CAN interface board.
- Four molded 9 pin DSUB connectors with thumbscrews for the CAN bus.
- Compatible with J1939, CANopen, NMEA 2000® and DeviceNet. Higher layer protocol translation handled by the user's application. For software support please see our Technical Associates products and our Software Download page (www.kvaser.com).

Support

Documentation, Kvaser CANlib SDK and drivers can be downloaded for free at www.kvaser.com/downloads.

Kvaser CANlib SDK is a free resource that includes everything you need to develop software for the Kvaser CAN interfaces. Includes full documentation and many program samples, written in C, C++, C#, Delphi, Visual Basic, Python and t programming language.

Kvaser CAN hardware is built around the same common software API. Applications developed using one device type will run without modification on other device types.

Technical Data	
CAN Channels	4
Certificates	CE, RoHS
Connector	One 25 pin DSUB Four 9 pin DSUB
Length	3000 mm
Material	ABS plastic
Operating Temperature Range	-30 to +85 °C
Weight	360 g