





Learn more about
this product




Your Gateway to Efficient Connectivity

Kvaser's OBD II Extension Cable is a highly durable extension cable of 10 metres in length with pin to socket connectors. The cable is made of OBD II high quality thermoplastic rubber to ensure excellent flexibility and resilience. All pins are connected.

 **Warranty**
2-Year warranty. See our general conditions and policies for details.

 **Support**
Free support for all products by contacting support@kvaser.com

 **EAN**
73-30130-00348-4

Major Features

- Molded OBD II (SAE J1962) pin connector, Type B (24 Volt).
- Molded OBD II (SAE J1962) socket connector, Type B (24 Volt).
- Gold plated pins on OBDII connectors for extra reliable contact.
- Termination is built in with a 120 Ohm terminating resistor.
- Available in other cable lengths.
- This cable can save wear and tear on your CAN interface's OBD2 connector.
- Compatible with J1939, CANopen, NMEA 2000® and DeviceNet. Higher layer protocol translation handled by the user's application. For software support please see our Technical Associates products and our Software Download page (www.kvaser.com).

Support

Documentation, Kvaser SDK and drivers can be downloaded for free at www.kvaser.com/downloads.

Kvaser SDK is a free resource that includes everything you need to develop software for the Kvaser CAN interfaces. Includes full documentation and many program samples, written in C, C++, C#, Delphi, Visual Basic, Python and t programming language.

Kvaser CAN hardware is built around the same common software API. Applications developed using one device type will run without modification on other device types.



Technical Data

CAN Channels	1
Certificates	CE, RoHS
Connector	OBD II (SAE J1962) Pin OBD II (SAE J1962) Socket
Length	10000 mm
Material	Durable thermoplastic rubber
Operating Temperature Range	-30 to +85 °C
Weight	875 g