





Learn more about  
this product




## Your Gateway to Efficient Connectivity

A Kvaser OBD II Adapter Cable connects any Kvaser CAN bus interface with a DSUB9 socket connector to any vehicle with an OBD II (J1962) connector. Supports K-Line.

 **Warranty**  
2-Year warranty. See our general conditions and policies for details.

 **Support**  
Free support for all products by contacting [support@kvaser.com](mailto:support@kvaser.com)

 **EAN**  
73-30130-00723-9

## Major Features

- Molded plug connector, for Type A (12 Volt) as well OBD II (SAE J1962) as Type B (24 Volt).
- Molded 9 pin DSUB socket connector with thumbscrews.
- 2500 mm (approx. 8 ft) long cable made of durable thermoplastic rubber.
- Designed for Kvaser’s High-Speed, Low-Speed and Single-Wire CAN interfaces.
- Perfect for Kvaser Memorator, Kvaser Leaf Professional, etc.
- Supports K-Line.
- Compatible with J1939, CANopen, NMEA 2000® and DeviceNet. Higher layer protocol translation handled by the user’s application. For software support please see our Technical Associates products and our Software Download page ([www.kvaser.com](http://www.kvaser.com)).

## Support

Documentation, Kvaser CANlib SDK and drivers can be downloaded for free at [www.kvaser.com/downloads](http://www.kvaser.com/downloads).

Kvaser CANlib SDK is a free resource that includes everything you need to develop software for the Kvaser CAN interfaces. Includes full documentation and many program samples, written in C, C++, C#, Delphi, Visual Basic, Python and t programming language.

Kvaser CAN hardware is built around the same common software API. Applications developed using one device type will run without modification on other device types.



## Technical Data

<b>CAN Channels</b>	1
<b>Certificates</b>	CE, RoHS
<b>Connector</b>	9 pin DSUB9 socket
<b>Length</b>	2500 mm
<b>Material</b>	Durable thermoplastic rubber
<b>Operating Temperature Range</b>	-30 to +85 °C
<b>Weight</b>	145 g