



Learn more about
this product



Your Gateway to Efficient Connectivity

A Kvaser OBD II Adapter Cable connects any Kvaser CAN bus interface with a DSUB9 socket connector to any vehicle with an OBD II (J1962) connector. Supports K-Line.



Warranty

2-Year warranty. See our general conditions and policies for details.



Support

Free support for all products by contacting support@kvaser.com



EAN

73-30130-00723-9

Major Features

- Molded plug connector, for Type A (12 Volt) as well OBD II (SAE J1962) as Type B (24 Volt).
- Molded 9 pin DSUB socket connector with thumbscrews.
- 2500 mm (approx. 8 ft) long cable made of durable thermoplastic rubber.
- Designed for Kvaser's High-Speed, Low-Speed and Single-Wire CAN interfaces.
- Perfect for Kvaser Memorator, Kvaser Leaf Professional, etc.
- Supports K-Line.
- Compatible with J1939, CANopen, NMEA 2000® and DeviceNet. Higher layer protocol translation handled by the user's application. For software support please see our Technical Associates products and our Software Download page (www.kvaser.com).

Support

Documentation, Kvaser CANlib SDK and drivers can be downloaded for free at www.kvaser.com/downloads.

Kvaser CANlib SDK is a free resource that includes everything you need to develop software for the Kvaser CAN interfaces. Includes full documentation and many program samples, written in C, C++, C#, Delphi, Visual Basic, Python and t programming language.

Kvaser CAN hardware is built around the same common software API. Applications developed using one device type will run without modification on other device types.

Technical Data

CAN Channels	1
Certificates	CE, RoHS
Connector	9 pin DSUB9 socket
Length	2500 mm
Material	Durable thermoplastic rubber
Operating Temperature Range	-30 to +85 °C
Weight	145 g