











# Your Gateway to Efficient Connectivity

Kvaser DB9-Power Inlet is a power injector developed for the Kvaser products which can be supplied via a CAN bus D-SUB 9 connector, such as Kvaser's Blackbird, Memorator, Ethercan and AirBridge series. With the Kvaser DB9-Power Inlet your Kvaser product can be supplied without interferring with the connected CAN-bus.

### **Warranty**

2-Year warranty. See our general conditions and policies for details.

#### Support

Free support for all products by contacting support@kvaser.com

III EAN

73-30130-00973-8



## Kvaser DB9-Power Inlet

#### **Major Features**

- Acts as a power injector with one powered D-SUB 9 socket and one non-powered D-SUB 9 plug connector.
- Connects to power supply using a standard 2.0 mm DC power connector.
- A complementary 12 V, 1 A power supply is included.
- Compatible with J1939, CANopen, NMEA 2000® and DeviceNet. Higher layer protocol translation handled by the user's application. For software support please see our Technical Associates products and our Software Download page (www.kvaser.com).

Su	pp	ort
----	----	-----

Documentation, Kvaser SDK and drivers can be downloaded for free at www.kvaser.com/downloads.

Kvaser SDK is a free resource that includes everything you need to develop software for the Kvaser CAN interfaces. Includes full documentation and many program samples, written in C, C++, C#, Delphi, Visual Basic, Python and t programming language.

Kvaser CAN hardware is built around the same common software API. Applications developed using one device type will run without modification on other device types.

Technical Data		
CAN FD	Yes	
Certificates	CE, RoHS	
Connector	1 socket, 1 plug D-SUB 9	
Dimensions	50 x 50 x 16 mm	
Length	27,500 mm	
Operating Temperature Range	-40 to +85 °C	
Weight	30 g	

