



Learn more about  
this product



## Your Gateway to Efficient Connectivity

The Kvaser Leaf v3 represents one of the easiest and lowest-cost methods of connecting a computer to a CAN bus network in order to monitor and transmit CAN and CAN FD data. With its standard USB type "A" connector and 9-pin D-SUB connector, the Leaf v3's sleek, ergonomically designed housing is both robust enough for every-day use and small and flexible enough to be used in space-constrained applications.

The Leaf v3 can handle up to 20 000 messages per second, each timestamped with a 50-microsecond accuracy. No external power is needed and galvanic isolation is standard.



### Warranty

2-Year warranty. See our general conditions and policies for details.



### Support

Free support for all products by contacting [support@kvaser.com](mailto:support@kvaser.com)



### EAN

73-30130-01424-4

## Major Features

- USB 2.0 CAN interface.
- Powered through the USB type "A" connector.
- Supports CAN FD, up to 8 Mbit/s.
- Quick and easy plug-and-play installation.
- Supports both 11-bit (CAN 2.0A) and 29-bit (CAN 2.0B active) identifiers.
- Supports silent mode for analysis tools – listen to the bus without interfering.
- 20 000 msg/s, each timestamped with a resolution of 50 µs.
- Fully compatible with applications written for other Kvaser CAN hardware with Kvaser CANlib.
- Support for SocketCAN.
- Supports simultaneous usage of multiple Kvaser interfaces.
- Compatible with J1939, CANopen, NMEA 2000® and DeviceNet. Higher layer protocol translation handled by the user's application. For software support please see our Technical Associates products and our Software Download page ([www.kvaser.com](http://www.kvaser.com)).

## Support

Documentation, Kvaser CANlib SDK and drivers can be downloaded for free at [www.kvaser.com/downloads](http://www.kvaser.com/downloads).

Kvaser CANlib SDK is a free resource that includes everything you need to develop software for the Kvaser CAN interfaces. Includes full documentation and many program samples, written in C, C++, C#, Delphi, Visual Basic, Python and t programming language.

Kvaser CAN hardware is built around the same common software API. Applications developed using one device type will run without modification on other device types.

## Technical Data

<b>CAN Bit Rate</b>	20 kbit/s to 1 Mbit/s
<b>CAN Channels</b>	1
<b>CAN FD Bit Rate</b>	Up to 8 Mbit/s
<b>CAN Transceivers</b>	MCP2561FD
<b>Certifications</b>	CE, RoHS
<b>Connector</b>	9-pin D-SUB USB type "A"
<b>Dimensions</b>	35 x 165 x 17 mm
<b>Error Frame Detection</b>	Yes
<b>Error Frame Generation</b>	No
<b>Galvanic Isolation</b>	Yes
<b>Operating Temperature Range</b>	-20 to +70 °C
<b>Power Consumption</b>	Typical 100 mA
<b>Silent Mode</b>	Yes
<b>Timestamp Resolution</b>	50 µs
<b>Weight</b>	110 g